



Sovereign

LABELLING MACHINES

'C' WRAP LABELLER



APPLIES A NARROW EDGE LEADING LABEL TO THE TOP, FRONT AND BASE FACE OF PACKS SIMULTANEOUSLY.

ALL STAINLESS STEEL CONSTRUCTION FEATURING THE MONARCH HIGH SPEED LABELLING HEAD.

PRODUCT TRANSPORTED BY SIDE DRIVE BELTS WITH HEIGHT AND TILT ADJUSTMENT TO ACCOMMODATE TAPERED SIDED CONTAINERS.

www.sovereign-labelling.co.uk



Sovereign

LABELLING MACHINES

SPECIFICATION	140 & 200 HEAD
Label Size	Up to 135mm or 195mm Wide
Speed	Up to 200 Products / Min
Label Reel Size	300mm Ø (76mm Ø core)
Electrical Supply	220/230V Single Phase AC (6 amps)

FEATURES:

1. Variable speed Servo driven applicator head.
2. Single point nip roller drive assembly for accurate label control.
3. Adjustable label roller web guides.
4. Optical label sensing - Available for all types of label media.
5. Thermal overprinting & Inkjet options.
6. Pitching & side driven product transfer belts with multiple adjustments for set up.
7. Base and Promo label application options.
8. Handwheel adjustment for lateral and vertical product set up.
9. Stainless steel construction.
10. 0-80 m/min standard web speed (Up to 200 ppm).
11. Label stopping accuracy to +/-0.5mm.
12. Designed and manufactured for low cost of ownership.
13. Software and machine compatible with thermal coders, printers, scanners and configurable to suit site specific requirements.
14. Simple to use operator touch-screen controls with I/O diagnostics and stored product set up recipes.
15. Additional specification *options* available to suit all applications.

Sovereign Labelling Machines Ltd

5, Wild Close, Oakwood Business Park, Clacton-on-Sea, Essex, CO15 4TL

Tel: 01206 304182

Email: sales@sovereign-labelling.co.uk